# therm@slate by cup/4 GROUP

THERMAL SOLAR NATURAL SLATE ROOFING



# ECOLOGY

### THERMOSLATE<sup>®</sup>, the power of nature

The THERMOSLATE® solar collector generates renewable, clean, environmentally-friendly energy.

# avoids the emission of 198 pounds of CO2 on average $ft^2$ It naturally heats 13 gallons of water per day

Utilizing natural slate as its main component where the production process is **completely environmentally friendly**. An analysis of the product's life cycle confirms natural slate as the most **ecological option for roofs**.



Comparison according to data published by the French database INIES on September 2014: http://www.base-inies.fr/Inies/Consultation.aspx

## CUP/4PIZARRAS NATURAL SLATE

 CUPA PIZARRAS is the world leader, with 16 natural slate quarries and 22 transformation plants. One out of three slates installed worldwide is a CUPA PIZARRAS slate.

• CUPA PIZARRAS is the only manufacturer that guarantees its slate and their traceability by means of **a unique bar code**. Our traceability system ensures each slate is monitored from the quarry to the end consumer, guaranteeing the factor that makes us stand out: **QUALITY**.

• Slate is a 100% natural product, directly extracted from the quarry. Slate withstands extreme temperatures and weather conditions.

# INVISIBLE



#### THERMOSLATE<sup>®</sup>: A system that needs to be shown

THERMOSLATE® solar collectors are completely undetectable once installed on a slate roof.



## ACTIVATE YOUR thermoslate





### INSTALLING INSTALL YOUR THERMOSLATE® SYSTEM IN JUST 3 HOURS

With its modular concept, **THERMO**SLATE<sup>®</sup> is fast and easy to integrate on your natural slate roof.



Request our complete installation guide, or go to THERMOSLATE.COM for more information.



# thermoslate

THERMAL SOLAR COLLECTOR | HOOK

SOLAR COLLECTOR DETAIL | INSTALLATION WITH HOOK



Slate dimensions	13 x 9, 14 x 9, 16 x 9
Collector nominal thickness	1 1/4"
Weight/m <sup>2</sup> (empty)	46 pounds
Fluid content/m <sup>2</sup>	10 US gallons

**THERMO**SLATE<sup>®</sup> thermal solar collectors, with a natural slate finish and installed with a hook, are compatible for perfect integration on roofs using 9" wide slate formats with varying lengths.

The result is the combination of a traditional natural slate roof and an innovative solar capturing system with a perfect look.





# thermoslate

THERMAL SOLAR COLLECTOR | NAILS

#### SOLAR COLLECTOR DETAIL | INSTALLATION SYSTEM WITH NAILS



Slate dimensions	20 x 10
Collector nominal thickness	1 1/4"
Weight/m <sup>2</sup> (empty)	46 pounds
Fluid content/m <sup>2</sup>	10 US gallons

The **THERMO**SLATE<sup>®</sup> solar collector system, with a natural slate finish and installed with a nail, integrates perfectly on natural slate roofs with 20 x 10 formats.

11111

**THERMO**SLATE<sup>®</sup> conserves the look and durability of a 1/4" thick natural slate and, at the same time, becomes an active element of the building or home, with great added value.





### INNOVATION

CUTTING-EDGE TECHNOLOGY ON YOUR NATURAL SLATE ROOF

Thanks to the efforts of **CUPAGROUP** R&D team, **THERMO**SLATE<sup>®</sup> is a solar collector system incorporating the latest technical innovations.



#### LIGHT AND ROBUST

Weighing just 44 US pounds, **THERMO**SLATE<sup>®</sup> is highly robust. This solar collector has been developed to be installed on any construction system.

### 100% WATERPROOF

A specific waterproofing kit certified by the CSTB, assures the total evacuation of water on the integration areas on slopes of over 3/12 pitch.



#### EFFICIENCY AND SAFETY

Maximum energy efficiency with a maximum operating temperature of 203° F, thanks to the properties of natural slate.

#### INSPIRED BY NATURE

The veins on the backs of tree leaves inspire the most efficient known energy absorption and fluid distribution system, which the **THERMO**SLATE<sup>®</sup> collector incorporate.

#### THERMOSLATE®, CERTIFIED QUALITY













One University Plaza suite 610 Hackensack, New Jersey 07601 United States of America Phone 201-880-9370 Fax 201-880-9372 info.thermoslate@cupagroup.com

#### THERMOSLATE® has been designed and developed by CUPAGROUP

